



SPEED (SECONDS)	MODEL NUMBER
5	5M5011CT
15	15M5011CT
30	30M5011CT
60	60M5011CT

SPECIFICATIONS								
WIRING	INPUT		OUTPUT		SHAFT ROTATION TO INCREASE VOLTAGE	TERMINAL CONNECTIONS		
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD		FOR INCREASING VOLTAGE AS VIEWED FROM ROTOR END		
SINGLE PHASE	120	50/60	0-140	MAX. AMPS	MAX. KVA	CW	INPUT	OUTPUT
				50	7.0		1-2	1-3

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #				UNITS		TITLE: SPEC. CONTROL DWG. VARIABLE TRANSFORMER M5011CT		
DECIMALS	Holes	ANGLES	DRAFT	IN	MM	DRAWN BY: TIM RAU DATE: 8/20/97		
.XX	.06	.002	1°	1-1/2°		CHECKER: DATE: WEIGHT APPROX. 78 LBS. CODE IDENT. NO. 83008		
MATERIAL:				ALL DIMENSIONS APPLY AFTER PLATING		ENGINEER: DATE: SCALE: .5=1 SHEET 1 OF 1		DWG. NO. 031-6197