

Shield connection terminal block - SKS 8 - 3240210

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Shield connection terminal block, for applying the shield to busbars

Why buy this product

- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm
- According to the requirements of the directive and standards for electrical equipment in potentially explosive areas, as components, shield connections are not able to gain certification. As such, shield connection clamps of type SKS can be used in the Ex area even without appropriate approval and identification.
- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm
- Three different mounting types supported: on NS 35 DIN rails, on busbars or directly on conductive mounting plates

Key Commercial Data

Packing unit	10 STK
GTIN	 4 046356 458658
GTIN	4046356458658

Technical data

General

Number of levels	1
Number of connections	1
Cable diameter	3 mm ... 8 mm
Color	silver
Open side panel	No

Dimensions

Length	18 mm
Width	12.4 mm
Height	26 mm

Connection data

Shield connection terminal block - SKS 8 - 3240210

Technical data

Connection data


Connection method	Spring-cage connection
Conductor cross section AWG min.	12
Conductor cross section AWG max.	8

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		7500651.22.01.00246
-----	--	---------------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>